

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7477

Set ¼ sec. post, from which
A fir, 8" dia., bears N.88°E., 51 lks.
A fir, 18" dia., bears S.5°W., 22 lks.

Douglas Co. Surveyors Office - John M. Powell - 8/1968 & 9/1968 - C.S. File 54/71-46

Reported as not found.
8/1968
Area cut & burnt. Good calls but not found.
9/1968
There is a skid Rd. that has taken stump out which lies on the side of a logging unit which is on the sec. line between 5, 8 at the location of the ¼ cor.

Wm. Ruppert - For: USFS - November 1977 - M 65-50

Set - Brass cap mkd: T31S R1W ¼ S5/S8 PLS 866 1977
14" D.Fir N.64°19'W., 91.8' "¼ S5 BT"
36" D.Fir N.29°19'E., 97.9' "¼ S5 BT"
6" D.Fir S.32°55'E., 66.4' "¼ S8 BT" (3rd BT added 1/27/1978 - WJR)

Leonard Herzstein - USDA Forest Service - Witness: Erica Barth - Jan. 4, 2001 - C.S. File 65/36-1

Found - 2½" dia. brass cap, properly mkd., firmly set, flush w/3 ft. mound of stone established by Ruppert in 1977 from which
36" dia., D.Fir, bears N.29°19'E., 97.9 ft. w/healed double blaze.
16" dia., D.Fir, bears S.12°31'W., 70.0 ft. (rec. S.32°55'E., 66.4 ft.) w/healed double blaze. This is the bearing & dist. reported to the Forest Service on the corner card signed by Wm. Ruppert in 1977 & etched on the BT tag I found on the ground beside the tree. I checked within ½ minute in bearing & 0.2 ft. in distance & I accept the information from Ruppert's corner card.
21" dia., D.Fir, bears N.64°19'W., 91.8 ft. with a healed double blaze.
New - A steel fence post bears N.89°W., 3.9 ft. projecting 4.0 ft. out of the ground w/Forest Service signs "Property Boundary" (#54-2) and "Attention" (#54-4) attached. continued next page

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - At the corner point, I used a magnetic declination of 17°E. in the staff compass to obtain a back sight bearing of S.89½°E., on a boundary post established by Ruppert in 1977, approx. 200 ft. away. I used my bearings & distances to confirm Ruppert's work. Trees are measured at the center of the root crown. Tree diameters are at breast height.

To reach the corner, take an old logging road, which is gated at Forest Service Road No. 1610 (Devil's Knob Road), northward 3/4 miles through sec. 8. At the curve at the end of the road, walk approx. 1000 ft. west on the section line to the corner.