

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7464

Set ¼ sec. post, from which
A fir, 10" dia., bears S.10°E., 11 lks.
A fir, 10" dia., bears N.37°W., 39 lks.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug./Sept. 1968 - C.S. File 54/71-100

Found - 10", now 22" D.Fir, N.37°W., 25.7 ft., scribe marks visible.
10" D.Fir, now stump, S.10°E., 7.3 ft., shows scar.
Also unrecorded Iron Pipe at ¼ Corner.
Set - Brass Cap at Cor. mkd COUNTY SURVEYORS T31S R1W
OFFICE 1968 ¼ S 32|S 33
Reblazed & rescribed -
22" D.Fir N.37°W., 25.7 ft. scribed "¼ S32 CS BT"
New BT - 13" D.Fir S.17°E., 15.9 ft. scribed "¼ S33 CS BT"
Note - NW BT is in fence corner running S-E-W.

Fd. Ok by Kaiser, 12/1992 - M116-30

Mark Smalley - For: Rsbg Resources Co - May 2003 - M142-27

Found - 1968 Douglas Co. Surveyors brass cap on iron rod.
16" Fir S.17°E., 15.9' healed. 1968
27" Fir N.37°W., 25.7' healer (orig.)
N-W BT is East-West-South fence corner.
Scribed- 15" Fir S.83°W., 26.1' "¼S BT"
13" Pine S.4°W., 29.4' "¼S BT"

Ron Quimby - For: Cow Creek - Nov. 2017 - M171-36

Found - Brass cap per 1968 renewal
10" now 31" D.Fir bears N.37°W., 25.7' healed scribe
(tree is in East-West-South fence corner)
13" now 18" D.Fir bears S.17°E., 15.9' healed scribe
15" now 16" D.Fir bears S.83°W., 26.1' healed scribe
13" now 16" Pine bears S.4°W., 29.4' healed scribe