

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7464-5

Set post, cor. secs. 28, 29, 32, & 33, from which
An Oak, 18" dia., bears N.27°E., 30 lks.
An Oak, 18" dia., bears N.80°W., 139 lks.
An Oak, 10" dia., bears S.22°W., 20 lks.
An Oak, 9" dia., bears S.57°E., 59 lks.

Douglas Co. Surveyors Office - John M. Powell - 8/1968 - C.S. File 54/71-101

Reported as not found.
All oaks in area have been opened.
Chained in from calls on creek two ways, could find no evidence of cor.

JA Hoffbuhr - Umpqua National Forest - Aug. 28. 1972 - M42-70

Set - 2"x30" Galv. Iron pipe with 3" Brass Cap stamped:
T 31 S R 1 W
S 29 | S 28
S 32 | S 33
Ore. Lic 222
1972

from which:
15" W.Fir bears N.41¼°E. 27.9 ft. scribed T31S R1W S28
RS 222 BT.
8" P.Pine bears S.50°E. 79.4 ft. scribed T31S R1W S33
RS 222 BT.
12" P.Pine bears S.16½°W. 45.5 ft. scribed T31S R1W S32
RS 222 BT.
8" D.Fir bears N.55¼°W. 28.3 ft. scribed T31S R1W S29
RS 222 BT.

John Ransom, USFS - Jonathan Drew - 1/16/2014 - C.S. File 65/85-9

Found - 3" brass cap (properly mkd) on 2½" iron pipe, projecting 1" above a ring of stone, near the center of a dirt private road
23" Fir N.41°30'E., 27.6 ft healed double blaze
9" P.Pine snag S.50°30'E., 79.0 ft healed detached face, leaning NW
21" P.Pine S.15°45'W., 45.4 ft healed double blaze, leaning SW
11" Fir N.56°15'W., 27.7 ft healed double blaze, leaning NW continued next page

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - A 9" P.Pine bears, S.36°15'E., - 76.7 ft. mkd. "T31SR1WS33" "BT" on a double blaze, with brass washer marked "LS2561" in lower blaze between B&T Red paint applied to BT faces and a 6" band at head height, BTs include BT & survey monument tags

Note - Corner falls on flat ground, in a road surface, surrounded by a wide ring of stones. Take county Rd 1A 3/4 mile to a pull out just past a bridge, opposite pullout is gated road, follow road over 1/2 mile to corner.

Brush cleared around monument and to BTs "LAND LINE" flagging tied on monument and guard posts

Measurements to accessories made with a LEICA 1103+ Total Station with reflectorless EDM to aluminum nail set at side center, basis of bearing from M81-59, being N.00°13'59"E., from an open traverse run between this corner and the S 1/16 Corner to the north. Measure = 1337.42' = Record.

Maintained property line North ¼ and West 1/8 miles