

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28 & 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7466  
-----

Set post, cor. secs. 20, 21, 28, & 29, from which  
An Oak, 15" dia., bears N.34°E., 79 lks.  
An Oak, 6" dia., bears N.15°W., 58 lks.  
An Oak, 12" dia., bears S.45°E., 48 lks.  
A pine, 12" dia., bears S.87°W., 59 lks.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1968 - C.S. File 54/71-87  
-----

Found - 15", now 21" W.Oak, N.34°E. 52.1 ft. shows good scar  
6", now 13" B.Oak, N.15°W. 38.3 ft., shows good scar  
12", now 16" W.Oak, S.45°E. 31.7 ft., not healed, rotten face.  
12" Pine, now 30" Stump, S.87°W., 38.9 ft., faint burnt scribe marks visible on Pine Log from stump.

Set - Brass Cap at cor. Mkd: County Surveyors T31S R1W  
Office S 20|S 21  
1968 S 29|S 28

Reblazed & Rescribed -  
16" W.Oak S.45°W., 31.7 ft. mkd. T31S R1W S28 CS BT.  
New BT - 9" W.Oak S.53°W., 56.8 ft. mkd. T31S R1W S29 CS BT.  
Note - This cor. lies about 4.0 north of old picket fence cor.