

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7468

Set ¼ sec. post, from which
An Oak, 6" dia., bears N.52°W., 130 lks.
An Oak, 24" dia., bears N.30°E., 129 lks.

Douglas Co. Surveyors Office - John M. Powell & Vernon "Ray" Tracy - Aug. 1968 - C.S. File 54/71-105

Found - Orig. 6", now 18" Oak, alive, N.52°W. 85.8 ft., opened, reverse "4" on piece, center decayed.
No trace On . NE BT.
Set - Brass cap at cor mkd. COUNTY SURVEYORS T31S R1W OFFICE 1968 ¼ S 20|S 21
New BTs- 15" Sugar Pine S.48½°W., 31.6 ft. mkd: ¼ S20 CS BT.
15" R.Cedar S.23°E., 64.6 ft. mkd: "¼ S21 CS BT".
This corner lies on moderate westerly slope in scattered oak-fir-cedar-pine.

Mark Smalley - For: Rsbg Resources Co - May 2003 - M142-28

Found - 1968 Douglas Co. Surveyors brass cap on an iron pipe.
18" Pine S.48½°W., 31.6' healed.
23" Cedar S.23°E., 64.6' partially healed scribed visible.
18" Oak N.52°W., 85.8' rotted face (orig.)
Scribed- 14" Oak N.42°W., 37.9' "¼S BT"

Jonathan B. Drew, II, USFS - Assisted by: Andrew Hillman, Survey Tech - 6/11/2015 - C.S. File 65/90-55

Found - 2½" brass cap on 1¼" galvanized iron pipe, projecting 10" above a mound of stone.
20" Oak with a previously opened & rotted face. (S.52°W., 85.8 ft. 1857)
Not verified a 36" Oak snag with a previously opened & rotted face fd in the approx. location of record (24" Oak) 1857 . No trace in 1968 (N.30°E., 85.1' 1857)
20" pine with scribe visible on a partially healed single blaze. (S.48°30'W., 31.6' 1968)
25" Cedar with a healed single blaze. (S.23°E., 64.6' 1968)
14" Oak with a healed single blaze, main stem of a 3 Oak clump. (N.42°W., 37.9' 2003)

continued next page

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height, add new nails to existing BT tags & add new tags where needed.
Lat: N 42°51'55.35274" Long: W 122°50'37.27067"
Ellipsoid Height: 2612.0 ft.
Datum: NAD_83(2011)(EPOCH:2010.0000)
Source: Direct occupation. RTK&STATIC GPS. OPUS corrected base.