TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7468

Set post, cor. secs. 16, 17, 20, & 21, from which
A fir, 24" dia., bears N.20°W., 32 lks.
A fir, 30" dia., bears N.40°E., 32 lks.
A fir, 12" dia., bears S.25°W., 32 lks.
A fir, 10" dia., bears S.47°E., 52 lks.
Built stone mound.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1968 - C.S. File 54/71-104

Found - Orig. 24" now 34" Fir snag, N.20°W., 21.1 ft., scribe marks visible on open blaze.
Orig. 30" now 38" Fir snag, N.40°E., 21.1 ft., shows scar. We do not open.
No trace other BTs.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1968 T31S R1W

S 17	S 16
S 20	S 21

New BTs- 9" Yew S.88°E., 1.2 ft. mkd: "T31S R1W S21 CS BT"
12" Maple N.5°E., 68.5 ft. mkd: "T31S R1W S16 CS BT"
18" D.Fir S.48½°W. 40.0 ft mkd: "T31S R1W S20 CS BT"
18" D.Fir N.54°W., 36.2 ft mkd: "T31S R1W S17 CS BT"
This corner lies about 75 ft. north of logging road.

Glenn S. Baughman - For: USFS - July 1978 - M70-28

Found - 1968 County Surveyors Brass cap.
12" Yew bears S.88°E., 1.2 ft.
15" Maple bears N.5°E., 68.5 ft.
18" D.Fir snag (5' high) bears S.48°30'W., 40.0 ft.
22" D.Fir stump bears N.54°W., 36.2 ft.
New BTs- 36" D.Fir bears S.6°W., 43.0 ft. scribed T31S R1W S20 BT.
20" D.Fir bears N.85°W., 65.3 ft. scribed T31S R1W S17 BT.