TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7469

Set ¼ sec. post, from which
An Oak, 10" dia., bears N.45°W., 11 lks.
An Oak, 12" dia., bears N.15°E., 35 lks.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - June 1966 - C.S. File 54/28-5

Found - 12" W.Oak, now 19" N.15°E., 23.1 ft. opened tree for scribe "S".
No trace of other BT.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T31S R1W
OFFICE 1968 ¼ S 17|S 16
New BT - 8" D.Fir N.27°W., 24.1 ft. scribed ¼ S17 CS BT.
Reblazed & Rescribed -
19" W.Oak N.15°E., 23.1 ft. scribed ¼ S16 CS BT.
Note - Logging road bears East 60.0 ft.

Jim Landrum, USFS & Deputy Douglas Co. Surveyors Office - Leonard Herzstein, Witness - June 21, 1983 - C.S. 62/10-11

Found - 1966 County brass cap, properly mkd. on 1¼" iron post, firmly set, projecting 12" above a 3 ft. dia. mound of stone.
Orig. B.Oak, 18", N.15°E., 23.8 ft (Rec. W.Oak, 23.1 ft. to face) with healed blaze and rescribed by Powell in 1966 with a healed blaze.
1966 BT, a 8" D.Fir stump, N.27°W., 24.1 ft. with a healed blaze.
New BT - 6" D.fir, S.38½°W., 10.2 ft. scribed "¼ S17 CS BT" on a single blaze.
Note - Corner is 60 ft. west of USFS Road #3131.