

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7470

Set post, cor. secs. 8, 9, 16, & 17, from which
An oak, 18" dia., bears S.12°W., 27 lks.
An oak, 10" dia., bears N.10°E., 33 lks.
An oak, 20" dia., bears N.5°W., 38 lks.
A pine, 24" dia., bears S.47°E., 43 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7545-6)

The cor. of secs. 8, 9, 16, & 17, located by reference to the orig. BTs.

At exact cor. point

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 8, 9, 16, & 17, with brass cap mkd

T31S R1W
S 8 | S 9
S 17 | S 16
1923

from which

- An oak, 10" dia., bears N.10°E., 33 lks., mkd: T31S R1W S9 BT. (old BT)
- A pine, 24" dia., bears S.47°E., 43 lks., mkd: T31S R1W S16 BT. (old BT)
- An oak, 18" dia., bears S.12°W., 27 lks., mkd: T31S R1W S17 BT. (Old BT)
- An oak, 20" dia., bears N.5°W., 38 lks., mkd: T31S R1W S8 BT. (old BT)

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Terry Connell - Sept. 2, 1966 - C.S. File 54/28-9

Found - Orig. 18" Oak, now dead, S.12°W., 17.8 ft.
Orig. 20" Oak, now 24" N.5°W., 25.1 ft. Tree opened scribe visible.
Orig. 24" Pine, now stump S.47°E., 28.4 ft. shows scar, stump has been moved.

GLO brass cap mkd. in 1923

New BTs- 12" D.Fir N.27°W., 29.4 ft. mkd: T31S R1W S8 CS BT.
11" D.Fir S.65°W., 110.0 ft. mkd: T31S R1W S17 CS BT
9" D.Fir N.70°E., 2.9 ft., mkd: T31S R1W S9 CS BT.
No tree in SE quad. This corner is at end of spur road on north edge of landing.

continued next page

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - L.E. Monrean - P. Earle -
Sept. 1, 1976 - C.S. File 59/24-7

Found - 1923 USGLO brass cap properly stamped.
Orig. 18" now 24" Oak snag, bears S.12°E., 17.8 ft.
Tree has well healed blaze.
A 12" now 16" D.Fir bears N.34°W., 29.4 ft., (Rec.
N.27°W.) to root crown. Tree leaning to the
Northwest has good blaze scribed "T31S R1W S8 CS
BT"
All other BTs are uprooted or gone.
New BTs- A 12" D.Fir bears N.11°E., 119.7 ft. Tree double
blazed & scribed "T31S R1W S9 CS BT"
A 3" Pine, bears S.22°W., 74.4 ft., scribed "X" 2"
high and 3" wide. (Approximately)
Set witness sign & post beside brass cap.
There are no trees suitable for marking in the SE quadrant.

William Ruppert - For: USFS - Nov. 1977 - M65-50

Found - 1923 GLO Brass cap, properly marked, on a 1" IP
12" D.Fir, N.09°46'E., 119.8 ft. good face.
23" Oak snag, S.10°02'W., 18.5 ft.
18" D.Fir, N.36°13'W., 29.9 ft. Good face.
Set - 6 ft. steel post, S.19°15'E., 60.4 ft.
6 ft. steel post, S.21°W., 67.7 ft.