

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6647)

-----  
Set post corner secs. 32, 33, 4 and 5, from which  
A Laurel 12" dia., bears S.74°E., 16 lks.  
A Fir 15" dia., bears S.88°W., 14 lks.  
A Fir 20" dia., bears N.40°E., 15 lks.  
A Pine 30" dia., bears N.30°W., 50 lks.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6705-06)

-----  
The corner of secs. 4, 5, 32 and 33, located by reference to the original bearing trees. From corner point,  
A Laurel 12" dia., bears S.74°E., 16 lks. dist. mkd. T31S R1W S4 BT. (Old BT)  
A Fir 15" dia., bears S.88°W., 14 lks. dist. mkd. T31S R1W S5 BT. (Old BT)  
A Fir 20" dia., bears N.40°E., 15 lks. dist. mkd. T30S R1W S33 BT. (Old BT)

The old bearing tree in sec. 32 is dead and fallen.  
At exact cor. point,  
Set an iron post 3 ft. long, 2" dia., 28" in the ground for cor. of secs. 4, 5, 32 and 33, with brass cap marked:

T30S R1W
S32   S33
S5   S4
T31S
1923

from which  
A Pine 18" dia., bears N.84°W., 58 lks. dist. mkd. T30S R1W S32 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Jan/Feb. 1968 - C.S. File 54/59-61

-----  
Found - GLO brass cap at cor., properly mkd. in 1923.  
15" D.Fir now 28", S.88°W., 9.2 ft., shows good scar.  
20" D.Fir now 34", N.40°E., 9.9 ft., shows good scar.  
18" Pine now stump, N.84°W., 38.3 ft.  
New BT - 12" D.Fir N.59°W., 36.3 ft. mkd. T30S R1W S32 CS BT  
Cor. lies approx. 65.0 ft. South of spring branch.

(Cont. Next Page)

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4 & 5; 32 & 33, T30-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Loyd R. Moffit, LS 944 - For: U.S. Forest Service - April  
1985 - C.S. File 63/8-6

-----  
Found - A 2½" brass cap on a 1½" iron pipe.  
32" Fir bears N.42°E., 10.8 ft., scar visible.  
20" Madrone bears S.74°E., 10.6 ft., scar visible.  
17" Pine bears S.01°E., 16.9 ft., scribe visible.  
(No record)  
Fir stump, bears S.88°W., 9.7 ft., scar visible.  
15" Fir bears N.56°W., 36.5 ft., scribe visible.  
New Bt - An 8" Fir which bears S.43°W., 35.6 ft. mkd. T31S  
R1W S5 BT.