

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7470

Set ¼ sec. post, from which
A cedar, 6" dia., bears S.70°E., 10 lks.
A fir, 24" dia., bears N.60°W., 39 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7545)

Proportional measurement.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked

$$\frac{1}{4} \frac{S \ 9}{S \ 16} \\ 1923$$

from which
A yew, 10" dia., bears S.81°W., 36 lks., mkd: ¼ S16 BT.
A fir, 8" dia., bears N.18°W., 23 lks., mkd: ¼ S9 BT.

Douglas Co. Surveyors Office - John M. Powell & Vernon "Ray" Tracy - Aug. 1968 - C.S. File 54/71-107

Found - 1923 GLO brass cap, bent over. Straightened & reset Brass cap.
10" Yew down, burnt, S.81°W., 23.8 ft. no scribe fd.
8" Fir now 13" snag, N.18°W., 15.2 ft. shows scar, we do not open.
New BTs- 42" D.Fir N.65°E., 44.0 ft., mkd: "¼ S9 CS BT"
7" Hemlock S.5°W., 95.0 ft., mkd: "¼ S16 CS BT"
This corner lies north of dry creek, course SW.

Glenn Baughman - For: USFS - July 1979 - C.S. 58/176-38

Found - 1" iron pipe with a 2½" brass cap set 8" above the ground & marked: ¼ S9 S16 1923 from which:
A 10" Yew, down & burnt, bears S.81°W., 23.8 ft.
A 13" D.Fir snag bears N.18°W., 15.2 ft.
A 42" D.Fir stump bears N.65°E., 44.0 ft.
A 10" Hemlock bears S.5°W., 95.0 ft.
New BTs- 14" D.fir bears N.32½°W., 114.6 ft. I marked "¼ S9 BT" on a double blaze & nailed a brass washer stamped "LS 536" into a lower blaze.

continued next page

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Loyd R. Moffit - For: USFS - Jan. 1986 - C.S. File 62/30-43

Found - 3/4" iron pipe with 2½" brass cap. (1923 GLO)
36" fir stump bears N.65°E., 44.0 ft. scar visible.
9" hemlock bears S.05°W, 95.0 ft. scribe visible.
Cedar snag (down) bears S.81°W., 23.8 ft. Has open
face. (Rec. Yew)
14" fir (dead) bears N.32°30'W., 114.6 ft. scribe
visible.
New BT - I marked a 3" fir BT which bears N.46°W., 5.5 ft.
scribed "X" BT. Nailed brass washer stamped L.S.
944 to BT scribe.