

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7578)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S}{S} \frac{4}{9}$
1923

from which

- A fir, 30" dia., bears S.1°W., 35 lks., mkd: 1/4 S9 BT.
- A fir, 30" dia., bears N.31°W., 42 lks., mkd: 1/4 S4 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Sept. 1968 - C.S. File 54/71-45

Found - GLO Brass Cap, properly marked in 1923.
30" now burnt stob, N.31°W., 27.7 ft., burnt face with taint scribe marks.
30", now 37" D.Fir S.1°W., 23.1 ft. shows good scar.
New BTs- 6" D.Fir N.41°W., 10.8 ft. scribed "1/4 S4 CS BT.
8" D.Fir S.59°E., 20.8 ft. scribed "1/4 S9 CS BT.
Note - This corner lies on a flat bench E. of ridge top about 15 chains, just E. of green timber.

FD. BC & 2 BTs by J. A. Hoffbuhr, 10/1972 - M47-9