

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7463  
-----

Set ¼ sec. post & built stone mound, from which  
An Oak, 30" dia., bears S.10°W., 18 lks.  
A Fir, 40" dia., bears S.80°E., 69 lks.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Sept. 1968 - C.S. File 54/71-52  
-----

Found - Unrecorded ½" Iron Pipe at ¼ Corner.  
40", now 48" D.Fir, S.80°E., 45.5 ft., faint bark scribe "¼S".  
30" Oak, now down, S.10°W., 11.9 ft., face rotten.  
Set - Brass Cap at Cor. Mkd: County Surveyors T31S R1W Office, 1968 ¼ S 33|S 34  
New BTs- 14" B.Oak N.52°W., 9.8 ft. mkd: ¼ S33 CS BT.  
6" D.Fir S.44°E., 12.2 ft. mkd: "¼ S34 CS BT.  
Note - Fence line bears West 12.6 ft. and North 4.5 ft.