

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27 & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 18 Page(s) 7465-6

Set post, cor. secs. 21, 22, 27, & 28, from which
A fir, 36" dia., bears N.42°W., 20 lks.
A fir, 24" dia., bears S.88°E., 20 lks.
A fir, 18" dia., bears S.30°W., 18 lks.
A fir, 18" dia., bears N.88°E., 15 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7539)

The cor. of secs. 21, 22, 27 and 28, located by reference to the original bearing trees.
At exact cor. point
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd
T31S R1W
S 21|S 22
S 28|S 27
1923
from which
A fir, 18" dia., bears N.88°E., 15 lks., mkd: T31S R1W S22 BT. (Old BT)
A fir, 24" dia., bears S.88°E., 20 lks., mkd: T31S R1W S27 BT. (Old BT)
A fir, 18" dia., bears S.30°W., 18 lks., mkd: T31S R1W S28 BT. (Old BT)
A fir, 36" dia., bears N.42°W., 20 lks., mkd: T31S R1W S21 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Oct. 1968 - C.S. File 54/71-70

Found - GLO Brass Cap, properly marked in 1922.
18", now 20" D.Fir, N.88°E., 9.9 ft. shows good face
24", now 28" D.Fir, S.88°E. 13.2 ft. shows good face
36", now 40" D.Fir, N.42°W. 13.2 ft. shows good face
18", now 19" D.Fir windfall, S.30°W., 11.9 ft. shows good face.
New BT - 6" W.Fir S.47°W., 5.3 ft. mkd: T31S R1W S28 CS BT.
This corner lies on steep west slope.