

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION West 1/4 Cor. Sec. 22, only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7540)

Mid point on W bdy. of Sec. 22, determined as hereinafter described.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 22 only, with brass cap marked

¼ S22
|
1923

from which

A cedar, 16" dia., bears N.21°E., 65 lks., mkd: ¼ S22 BT.

A fir, 34" dia., bears S.10°E., 12 lks., mkd: ¼ S22 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Oct. 1968 - C.S. File 54/71-69

Found - Brass cap and 2 BTs.
16" cedar now 24" N.44°E., 49.9 ft. - Note: record is N.21°E., 42.9 ft., opened and fd scribing of (¼S21BT)

34" D.Fir now 44" S.10°E., 7.9 ft., shows a good face. Note: this BT is referred, as a BT to the ¼ cor. Of S21 only. By GLO field notes

We found the brass cap for ¼ cor. Of S21 only in place of the ¼ cor. S22 only. We switch the brass caps around so they are in the right places. Now reads as follows:

Reset - GLO brass cap at the ¼ cor. of S22 only, (properly) mkd.

Rescribed BT -

24" Cedar N.44°E., 49.9 ft. rescribed: ¼ S22 CS BT.

Note - This ¼ cor. of S22 only lies 7.9 ft. S of ¼ Cor. Sec. 21 only.