

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION West 1/4 Cor. Sec. 15, only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7542-3)

Mid point bet. the closing cor. of secs. 15 & 22, and the closing cor. of secs. 10 & 15, determined as hereinafter described.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 15 only, with brass cap marked

¼ S15
|
1923

from which

A fir, 28" dia., bears N.40°E., 67 lks., mkd: ¼ S15 BT.

A fir, 4" dia., bears S.53°E., 44 lks., mkd: ¼ S15 BT.

Douglas Co. Surveyors Office - John M. Powell & crew - 8/1968
- C.S. File 54/71-111

Reported as Fd. OK

1923 GLO BC & BTs alive & in good cord. This cor. lies 87.8 ft. S. of ¼ 16 only.

Jonathan B. Drew, II, USFS - 5/4/2015 - C.S. File 65/90-16

Found - 2½" GLO brass cap on 1" iron pipe, projecting 4" above a mound of stone. I paint iron pipe red to protect from rusting further.

A 47" Fir with a healed single blaze, rec. (N40°E., 44.2 ft.) 1922

A 27" Fir with a healed single blaze, rec. (N.53°E., 29.0 ft.) 1922

No new accessories needed.

Corner maintenance/other info - Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height, add new nails to existing BT tags & add new tags where needed.

Geodetic coordinates -

Lat: N. 42°52'46.199" Long: W. 122°49'25.495"

Datum - WGS 84

Source - Cell phone GPS, for Navigation to corner.