

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 10 only, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7575)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor. of sec. 10 only, with brass cap marked

1/4 S 10
1923

from which

- A fir, 48" dia., bears N.58°E., 48 lks., mkd: 1/4 S10 BT.
- A fir, 60" dia., bears S.48°E., 93 lks., mkd: 1/4 S10 BT.

Douglas Co. Surveyors Office - John M. Powell & Vernon "Ray" Tracy - Aug. 1968 - C.S. File 54/71-119

-
- Found - 1923 GLO brass cap, in place.
 - 48" D.Fir, now burnt snag, N.58°E. 31.7 ft., opened for fragments of scribe.
 - 60" D.Fir, now down, S.48°E. 61.4 ft.
 - New BT - 8" D.Fir N.55°E., 16.5 ft. scribed "1/4 S10 CS BT".
 - 7" D.Fir S.69°E., 29.2 ft. scribed "1/4 S10 CS BT".
 - Note - This corner lies 129.4 ft. S of corner sec. 9 only.