

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 400542

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 9 only, East

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7575-6)

-----  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor. of sec. 9 only, with brass cap marked

1/4 S 9 |  
1923

from which

- A fir, 36" dia., bears S.75°W., 37 lks., mkd: 1/4 S9 BT.
- A fir, 36" dia., bears N.30°W., 38 lks., mkd: 1/4 S9 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1968 - C.S. File 54/71-118

-----  
Found - 1923 GLO brass cap at 1/4, in place.  
36", now 39" D.Fir, S.75°W. 24.1. ft., shows good scar.  
36", now 39" D.Fir, N.30°W. 25.1 ft., shows good scar.

New BTs- 9" Cedar S.72°W., 5.6 ft. scribed "1/4 S9 CS BT".  
This corner lies 129.4 ft. north of corner Sec. 10 only. All Trees Tagged.