

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION CC Cor. Secs. 3 & 10 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7576)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 3 & 10 only, with brass cap mkd

	T31S
S 9	S 3
	-----
	S 10
	R1W
	1923

from which

- A fir, 26" dia. bears N.56°E., 23 lks. mkd: T31S R1W S3 BT
- A yew, 14" dia. bears S.45°E. 58 lks. mkd: T31S R1W S10 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1968 - C.S. File 54/71-93

-----  
Found - 14" Yew S.45°E., 38.3 ft., scribe visible, T31S R1W S10 BT.

26" D.Fir, now down, N.56°E., 15.2 ft.

No trace of 1923 GLO Brass Cap, area logged. Used metal finder to look for cap with no results.

Set - Brass Cap at Cor. Mkd: County Surveyors T31S R1W

Office	S 9   S 3
1968	S 10

New BTs- 11" Cedar N.37°W., 96.3 ft. mkd: T31S R1W S9 CS BT.

10" D.Fir N.36°E., 105.3 ft. mid. T31S R1W S3 CS BT.

Note - This corner lies on east edge of swampy area.

I could not chain between corners because of water.