

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 400604

PRIMARY CORNER DESCRIPTION CC Sec. 4 & 9 only, (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7576-7)

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 4 & 9 only, with brass cap mkd

T31S
S 4 | S 3
S 9 |
R1W |
1923

from which

A fir, 14" dia. bears S.41°W., 55 lks. mkd: T31S R1W S9 BT
A fir, 18" dia. bears N.39°W., 23 lks. mkd: T31S R1W S4 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1968 - C.S. File 54/71-92

Found - 14" D.Fir, now burnt stob, N.39°W., 15.2 ft., faint scribe visible, "T31S R1W"
14" D.Fir, now burnt stob, S.41°W., 36.3 ft., found scribing.

GLO Brass Cap, properly marked in 1923.

New BTs- 9" D.Fir N.68°W. 18.9 ft. mkd T31S R1W S4 CS BT.
9" D.Fir S.66°W. 9.7 ft. mkd. T31S R1W S9 CS BT.
11" D.Fir East 7.3 ft. mkd: T31S R1W S3 CS BT.