

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 3 only, West

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7579)

-----  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor. of sec. 3 only, with brass cap marked

1/4 S3  
|  
1923

from which

A fir, 24" dia., bears N.69°E., 17 lks., mkd: 1/4 S3 BT.

A fir, 36" dia., bears S.52°E., 44 lks., mkd: 1/4 S3 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1968 - C.S. File 54/71-94

-----  
Found - GLO Brass Cap for 1/4 Corner, properly marked in 1923. 24", now 28" D.Fir, N.69°E., 11.2 ft., shows good scar.

36" D.Fir, now stump, S.52°E., 29.0 ft., opened for scribe "BT".

New BT - 6" Hemlock S.15°E. 56.4 ft. mkd. 1/4 S3 CS BT.

Note - This corner lies 267.9 ft. south of 1/4 Cor. Sec. 4 only, which was found in good condition, 1923 Brass Cap and BTs OK.