

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6648)

-
- A Fir 6" dia., corner secs. 33, 34, 3 and 4, from which
 - A Fir 12" dia., bears S.85°W., 42 lks.
 - A Fir 10" dia., bears N.20°W., 27 lks.
 - A Fir 30" dia., bears S.35°E., 18 lks.
 - A Fir 12" dia., bears N.5°E., 23 lks.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6708)

Point for the old cor. of secs. 3, 4, 33 and 34, which I locate with reference to the original bearing trees. I now change this cor. to refer to secs. 33 and 34 only. Set an iron post 3 ft. long, 2" dia., 28" in the ground for cor. of secs. 33 and 34 only, with brass cap mkd:

T30S | R1W
S33 | S34

T31SR1W
S3
1923

from which

- A Fir 40" dia., bears N.72°E., 89 lks. dist. mkd. T30S R1W S34 BT. (New BT.)
- A Fir 38" dia., bears N.59°W., 33 lks. dist. mkd. T30S R1W S33 BT. (New BT)
- A Fir 30" dia., bears S.35°E., 18 lks. dist. mkd. T31S R1W S3 BT. (Old BT)
- A Fir 12" dia., bears S.85°W., 42 lks. dist. mkd. T31S R1W S4 BT. (Old BT)

I obliterate the marks on the bearing trees referring to secs. 3 and 4.

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 1967 - C.S. File 54/59-11

Found - GLO brass cap, properly marked in 1923.
38" D.Fir, now dead, N.59°W., 21.8 ft., scribe visible, "T30 RW BT"
30" D.Fir, now down, S.35°E., 11.9 ft.
40" D.Fir, now stump, N.72°E., 58.7 ft.
No trace of SW. BT.

New BTs- 5" S.Fir N.21°W., 6.8 ft. mkd. T30S R1W S33 CS BT.
12" S.Fir N.24°E., 21.5 ft. mkd. T30S R1W S34 CS BT.

Cor. lies approx. 25.2 ft. West of creek.