

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 438100

PRIMARY CORNER DESCRIPTION Sec. Cor. of 3 & 4 only, T32-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 18 Page(s) 7487)

-----  
(A point 237 lks. W. of 1/4 sec. cor. of S.34) Set a basalt stone 18x8x6 ins., 12" in the ground for cor. to secs. 3 and 4, mkd. with 3 notches on E. and W. edges, from which  
A Fir 5" dia., bears N.47°E., 9 lks. dist. mkd. T31S R1W S34 BT.  
A B.Oak 6" dia., bears S.19°W., 28 lks. dist. mkd. T32S R1W S4 BT.  
A Matherone 10" dia., bears S.35°E., 20 lks. dist. mkd. T32S R1W S3 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - July/Aug. 1968 - C.S. File 54/71-24

-----  
Found - No trace of stone or SW. BT.  
10" now 14" Laurel S.35°E., 13.2 ft., shows scar.  
5" now 8" D.Fir N.47°E., 5.9 ft., rotten face, scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 1 W

S 34

S 4 | S 3

T 32 S

1968

New BTs- 6" Live Oak S.74°W., 35.4 ft. mkd. T32S R1W S4 CS BT  
8" Live Oak N.51°W., 26.2 ft. mkd. T31S R1W S34 CS BT.

SE. BT OK and tagged.