

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7566)

-----  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  $\frac{S\ 22}{S\ 27}$   
1923

from which

- A fir, 12" dia., bears N.48°E., 12 lks., mkd: 1/4 S22 BT.
- A fir, 9" dia., bears S.39°W., 16 lks., mkd: 1/4 S27 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Oct. 1968 - C.S. File 54/71-71

-----  
Found - GLO Brass Cap, properly marked in 1922.  
12", now 16" D.Fir, N.48°E., 7.9 ft. shows good face  
9", now 12" D.Fir, S.39°W., 10.5 ft., shows face.  
Rescribed: 16" D.Fir N.48°E., 7.9 ft. mkd: 1/4 S22 CS BT.  
12" D.Fir S.39°W., 10.5 ft. mkd: 1/4 S27 CS BT.  
Note - No other trees as good as these for scribing.  
This cor. lies 60 ft. south of E-W. blazed line & 20' W of creek.