

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7568-9)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S 15
S 22
1923

from which

- A fir, 40" dia., bears N.71°E., 22 lks., mkd: 1/4 S15 BT.
- A fir, 20" dia., bears S.72°W., 23 lks., mkd: 1/4 S22 BT.

Douglas Co. Surveyors Office - John M. Powell & Vernon "Ray" Tracy - Aug. 1968 - C.S. File 54/71-108

Found - 1922 GLO Brass Cap at Cor., properly marked.
20", now 29" R.Fir S.72°W. 15.2 ft., shows good scar.

40" D.Fir now stump, N.71°E. 14.5 ft. scribe visible
New BT - 27" R.Fir N.83°E. 25.4 ft. mkd: "1/4 S15 CS BT".

Note - Rd bears North 70.0