

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 3 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6709)

-----  
Set an Iron post 3 ft. long, 1" dia., 28" in the ground for ¼ sec. cor. of sec. 3 only, with brass cap mkd:

¼ S 3  
1923

from which

A Fir 30" dia., bears S.84°W., 342 lks. dist. mkd. ¼ S3 BT  
No other trees within limits; raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.

Douglas Co. Surveyors Office - John M. Powell, and crew - July 1968 - C.S. File 54/59-119

-----  
Found - GLO brass cap, properly mkd. in 1923.  
30" D.Fir now snag, S.84°W., 239.0 ft. (Rec. 225.7 ft.), opened for scribe.

RESET brass cap at orig. distance from ¼ cor. of sec. 34 only (which is a brass cap in good condition) 180.2 ft. East of ¼ corner in a large mound of stone.

No trees within reason in South quad.

New BT - 18" D.Fir N.59°W., 129.0 ft. mkd. ¼ S3 CS BT.

Mound of stone 2x2x2, South 19.2 ft. of ¼ corner.

Cor. lies on East slope, in a large opening, all rock.