

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 443700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only, T30-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6648)

Set ¼ sec. post and built stone mound, from which
A Fir 36" dia., bears N.89 3/4°E., 383 lks.
A Fir 20" dia., bears S.89°E., 405 lks.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6709-10)

The old ¼ sec. cor., indicated by small mound of stone in which the post was originally set. The original bearing trees are dead and fallen. I now change this cor. to refer to sec. 34 only. In place of the decayed post, Set an iron post 3 ft. long, 1" dia., 8" in the ground surrounded by a mound of stone, 3 ft. base, 1½ ft. high, for ¼ sec. cor. of sec. 34 only, with brass cap mkd: ¼ S 34
1923

from which
An Oak 15" dia., bears N.58°E., 123 lks. dist. mkd. ¼ S34 BT.
A Fir 24" dia., bears N.13°W., 267 lks. dist. mkd. ¼ S34 BT.

Found brass cap in good condition - DCSO, John Powell, July 1968 - C.S. File 54/59-120