

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7563)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 27 | S 26
1923

from which

- A fir, 8" dia., bears N.11°E., 28 lks., mkd: 1/4 S26 BT.
- A fir, 6" dia., bears N.36°W., 13 lks., mkd: 1/4 S27 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug. 1968 - C.S. File 54/71-117

Found - 1922, GLO Brass Cap, out of ground on steep west slope.

8", now 15" D.Fir, N.11°E. 18.5 ft., shows good scar.

6", now 9" D.Fir, N.36°W. 8.6 ft., opened for scribe "B".

Reset - Brass Cap at 1/4 corner in Mound of Stone.

New BT - 7" D.Fir N.64°E., 4.6 ft. scribed 1/4 S27 CS BT.