

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7564)

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 22, 23, 26, & 27, with brass cap mkd

T31S R1W
S 22|S 23
S 27|S 26
1923

from which

- A fir, 24" dia. bears N.18°E. 51 lks. mkd: T31S R1W S23 BT
- A fir, 30" dia. bears S.33°E. 31 lks. mkd: T31S R1W S26 BT
- A fir, 36" dia. bears S.41°W. 33 lks. mkd: T31S R1W S27 BT
- A fir, 28" dia. bears N.33°W. 23 lks. mkd: T31S R1W S22 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Oct. 1968 - C.S. File 54/71-72

Found - GLO Brass Cap, properly marked in 1923.
24", now 28" D.Fir, N.18°E., 33.6 ft shows good scar
30", now 36" D.Fir, S.33°E., 20.4 ft shows good scar
28", now 34" D.Fir N.33°W., 15.2 ft. shows good scar
36", now D.Fir Stob, S.41°W., 21.0 ft., shows good scar.

New BT - 7" D.Fir S.54°W., 16.3 ft. mkd: T31S R1W S27 CS BT.
All other bearing trees tagged.