

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22 & 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7567)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 14, 15, 22, & 23, with brass cap mkd

T31S R1W  
S 15 | S 14  
S 22 | S 23  
1923

from which

- A fir, 8" dia. bears N.36°E., . 29 lks. mkd: T31S R1W S14 BT
- A fir, 10" dia. bears S.51°E. 34 lks. mkd: T31S R1W S23 BT
- A fir, 22" dia. bears S.17°W. 34 lks. mkd: T31S R1W S22 BT
- A fir, 18" dia. bears N.65°W. 33 lks. mkd: T31S R1W S15 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Sept. 1968 - C.S. File 54/71-126

-----  
Found - GLO Brass Cap, properly marked in 1922.  
8", now 14" D.Fir, N.36°E. 19.1 ft. shows good scar.  
18", now 24" R.Fir, N.65°W., 21.8 ft., scribe visible.  
10", now 14" R.Fir, S.51°E., 22.4 ft., scribe marks partially visible.  
22" R.Fir, now stump, S.17°W., 22.4 ft., scribe visible.  
New BT - 30" D.Fir South 26.8 ft. scribed T31S R1W S22 CS BT.