

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7569)

-----  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  
S 15 | S 14  
1923

from which

- A fir, 24" dia., bears S.37°E., 13 lks., mkd: 1/4 S14 BT.
- A fir, 30" dia., bears S.45°W., 13 lks., mkd: 1/4 S15 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug/Sept. 1968 - C.S. File 54/71-128

- 
- Found - GLO Brass Cap properly marked in 1922.  
24" D. Fir, now stump, S.37°E., 8.6 ft., shows good scar.  
30" D. Fir, now stump, S.45°W., 8.6 ft., shows scribe visible "BT".
- New BTs- 11" R. Fir N.23°E., 19.0 ft. scribed 1/4 S14 CS BT.  
13" Hemlock N.71°W., 36.5 ft. scribed 1/4 S15 CS BT.