

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7573)

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 2, 3, 10, & 11, with brass cap mkd

T31S	R1W
S 3	S 2
S 10	S 11
1923	

from which

- A fir, 40" dia. bears N.46°E., 46 lks. mkd: T31S R1W S2 BT
- A fir, 40" dia. bears S.8°E., 20 lks. mkd: T31S R1W S11 BT
- A fir, 9" dia. bears S.27°W., 59 lks. mkd: T31S R1W S10 BT
- A fir, 42" dia. bears N.33°W., 94 lks. mkd: T31S R1W S3 BT

Douglas Co. Surveyors Office - John M. Powell - 9/1968 - C.S. File 54/71-123

Reported as not found.

Brushed line & chained from location tag on Rd., found some large uprooted trees but no evidence of cor. approx location of cor. falls in cleared area for skid trails.