

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7574)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 3 | S 2
1923

from which

A fir, 10" dia., bears S.83°E., 27 lks., mkd: 1/4 S2 BT.

A laurel, 8" dia., bears S.52°W., 25 lks., mkd: 1/4 S3 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Sept. 1968 - C.S. File 54/71-48

Found - GLO Brass Cap at 1/4 Cor. Mkd. properly in 1923.
10" D.Fir, now burnt stump, S.83°E., 17.6 ft., scribe visible.

No trace of SW bearing tree.

New BTs- 7" Laurel S.46°E., 9.0 ft. mkd: "1/4 S2 CS BT".

5" Laurel S.55°W., 17.1 ft. mkd: "1/4 S3 CS BT".

Note - This corner lies in old unit on steep E slope about 150 ft. west of draw & 70' south of open rocky slope.