

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION C C for secs. 2 & 3 only, (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6710)

Set an iron post 3 ft. long, 2" dia., 28" in the ground for closing cor. of secs. 2 and 3, with brass cap marked:

T30S R1W

S34

S3 | S2
T31S | R1W
C C
1923

from which

A Fir 40" dia., bears S.24°E., 24 lks. dist. mkd. T31S R1W S2 CC BT.

A Fir 38" dia., bears S.27°W., 14 lks. dist. mkd. T31S R1WS 3 CC BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - July 1968 - C.S. File 54/59-118

Found - GLO brass cap at cor., properly mkd. in 1923.
40" now 40" D.Fir, S.24°E., 15.8 ft., shows good scar.

38" D.Fir now stob, S.27°W., 9.2 ft., shows good scar.

New BT - 7" Maple S.48°W., 29.5 ft. mkd. T31S R1W S3 CC CS BT.

SE. BT OK and tagged.

Cor. lies on W. slope 207.5 ft. W. of sec. cor. 34 & 35, T30S R1W.