

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 539100

PRIMARY CORNER DESCRIPTION A P on So. Bdy. Sec. 35, W. of ¼ cor.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 18 Page(s) 7480 and Pgs. 7484-85)

Set a basalt stone 18x12x8 ins., 12" in the ground for ¼ sec. cor. about 300 ft. above creek, mkd. ¼ on W. face, from which
A Fir 14" dia., bears N.67°E., 24 lks. dist. mkd. ¼ S BT.
A Fir 6" dia., bears S.45°E., 13 lks. dist. mkd. ¼ S BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7518)

The old ¼ sec. cor., which is a basalt stone, firmly set, 6x12x8 ins. above ground, marked ¼ on N. face; from which
A Fir 14" dia., bears N.67°E., 24 lks. dist. mkd. ¼ S BT.
(Old BT)

The old bearing tree SE. of cor. is dead.
I now change this cor. to an angle point; obliterate the marks on the stone and bearing tree and re-mark the tree AP and the stone A P on N. face, from which
A Fir 14" dia., bears S.80°E., 37 lks. dist. mkd. AP BT.
(New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Aug. 1968 - C.S. File 54/71-41

Found - Stone, 6x12x8 at Angle Point.
14" D.Fir now stob, N.67°E., 15.8 ft., shows good scars.
14" D.Fir now stob, S.80°E., 24.4 ft., scribe visible, "AP BT".

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 1 W
 A P
 T 32 S
 1968

New BTs- 14" D.Fir S.20°W., 33.7 ft. mkd. AP CS BT.
 16" D.Fir S.30°E., 22.6 ft. mkd. AP CS BT.
Cor. lies 37.0 ft. West of ¼ corner Sec. 35, T31-1W.