

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7568)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S 14
S 23
1923

from which

A fir, 8" dia., bears N.15°E., 12 lks., mkd: 1/4 S14 BT.
A fir, 20" dia., bears S.65°W., 20 lks., mkd: 1/4 S23 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug/Sept. 1968 - C.S. File 54/71-127

Found - GLO Brass Cap at 1/4 Corner, properly marked in 1922. 20" D.Fir, now stump, S.65°W., 13.2 ft., opened for scribe "S23".

No trace of 8" Fir N.15°E.

This corner lies in old clear cut unit. No trees for BTs.

Set - 3/4" I.Rod S.65°W., 11.2 ft.

3/4" I.Rod. S.65°W., 5 ft

Location tag on BT stump S.65°W., 13.2 ft.

This corner lies 187.0 ft. west of deep ravine.