

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7571)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 11}{S\ 14}$

from which

A fir, 12" dia., bears S.4°E., 25 lks., mkd: 1/4 S14 BT.

A fir, 36" dia., bears N.18°W., 16 lks., mkd: 1/4 S11 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug./Sept. 1968 - C.S. File 54/71-122

Found - GLO Brass Cap at 1/4 corner, properly marked in 1923. 36", now 44" D.Fir, N.18°W. 10.5 ft., shows good face.

No trace of SE Bearing Tree.

New BT - 10" Yew S.30°W., 35.6 ft. scribed 1/4 S14 CS BT.

Note - Logging Road bears west 330 feet.