

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7552-3)

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 23, 24, 25, & 26, with brass cap mkd

T31S R1W
S 23|S 24
S 26|S 25
1923

from which

- A fir, 20" dia. bears N.80°E. 107 lks mkd: T31S R1W S24 BT
- A fir, 16" dia. bears S.40°E. 34 lks. mkd: T31S R1W S25 BT
- A fir, 30" dia. bears S.63°W. 19 lks. mkd: T31S R1W S26 BT
- A fir, 32" dia. bears N.23°W. 37 lks. mkd: T31S R1W S23 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Sept. 1968 - C.S. File 54/71-63

Found - GLO Brass Cap at Sec. Cor., properly marked in 1923.
16", now 19" D.Fir, S.40°E., 22.4 ft., shows good scar.
40", now 36" D.Fir, S.63°W., 12.5 ft., shows good scar.
32", now 38" D.Fir, N.23°W., 24.4 ft., pitched over, scribe visible.
20" D.Fir, now snag, N.80°E., 70.6 ft. scribe visible.

New BT - 6" D.Fir N.52°E., 24.5 ft. scribed S24 CS BT.

Note - No other trees in reasonable distance.
This corner lies on small spur running about S.50°W., top of spur rocky.