

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7554-5)

-----  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  
S 23 | S 24  
1923

from which

- A fir, 7" dia., bears N.12°E., 11 lks., mkd: 1/4 S24 BT.
- A fir, 8" dia., bears S.14°W., 27 lks., mkd: 1/4 S23 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Sept. 1968 - C.S. File 54/71-62

-----  
Found - GLO Brass Cap, properly marked in 1923, out of ground.

7", now 14" D.Fir, N.12°E., 7.3 ft., opened for scribe.

8", now 20" D.Fir, S.14°W., 17.8 ft., shows good scar.

Reset - GLO Brass Cap for 1/4 corner.

New BT - 20" D.Fir N.54°W., 8.7 ft. scribed "1/4 S23 CS BT".  
All trees tagged.