

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7555)

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 13, 14, 23, & 24, with brass cap mkd

T31S R1W  
S 14|S 13  
S 23|S 24  
1923

from which

- A fir, 12" dia. bears N.66°E. 53 lks. mkd: T31S R1W S13 BT
- A fir, 12" dia. bears S.82°E. 26 lks. mkd: T31S R1W S24 BT
- A fir, 14" dia. bears S.18°W. 40 lks. mkd: T31S R1W S23 BT
- A fir, 12" dia. bears N.26°W. 29 lks. mkd: T31S R1W S14 BT