

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7557)

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 11, 12, 13, & 14, with brass cap mkd

T31S R1W
S 11|S 12
S 14|S 13
1923

from which

- A fir, 14" dia. bears N.45°E. 39 lks. mkd: T31S R1W S12 BT
- A fir, 36" dia. bears S.63°E. 18 lks. mkd: T31S R1W S13 BT
- A fir, 14" dia. bears S.58°W. 37 lks. mkd: T31S R1W S14 BT
- A fir, 12" dia. bears N.13°W. 28 lks. mkd: T31S R1W S11 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Aug/Sept. 1968 - C.S. File 54/71-120

Found - GLO Brass Cap, properly marked in 1923
36" D.Fir, now 38" Snag, S.63°E. 11.9 ft., opened & found scribing.
14" Fir, now stump hole, S.58°W. 24.4 ft.
No trace of BTs in the north. Corner lies in old burn.

New BTs- 8" D.Fir S.12°E., 12 ft. scribed T31S R1W S13 CS BT.
7" D.Fir S.68½°W., 15.2 ft. scribed T31S R1W S14 CS BT.
6" D.Fir N.68°W., 12.4 ft. scribed T31S R1W S11 CS BT.
7" D.Fir N.7°E., 31.7 ft. scribed T31S R1W S12 CS BT

Fd. Ok 3/5/1991 By Bruce Shaner, C.S. File 63/129-5