

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 18 Page(s) 7483-84)

Set a basalt stone 18x10x6 ins., 12" in the ground for cor. to secs. 1 and 2 mkd. with 1 notch on E. and 5 notches on W. edges, from which

- A Fir 20" dia., bears N.3°W., 45 lks. dist. mkd. T31S R1W S36 BT.
- A Fir 15" dia., bears S.10°W., 111 lks. dist. mkd. T32S R1W S2 BT.
- A Fir 10" dia., bears S.10°E., 103 lks. dist. mkd. T32S R1W S1 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7520)

The cor. of secs. 1 & 2 only, which is a basalt stone firmly set, 6x10x6 ins. above ground, marked with 1 notch on E. and 5 notches on W. edge, from which

- A Fir 20" dia., bears N.3°W., 45 lks. dist. mkd. T31S R1W S36 BT. (Old BT)
- A Fir 15" dia., bears S.10°W., 111 lks. dist. mkd. T32S R1W S2 BT. (Old BT)
- A Fir 10" dia., bears S.10°E., 103 lks. dist. mkd. T32S R1W S1 BT. (Old BT)

Obliterate the marks on the bearing tree referring to S 36.

Douglas Co. Surveyors Office - John M. Powell, and crew - July/Aug. 1968 - C.S. File 54/71-28

Found - Stone mkd. with 5 notches & C.C.
 20" now 37" D.Fir N.3°W., 29.7 ft., tree opened, scribe visible.
 10" now 10" D.Fir S.10°E., 68.0 ft. (slope dist.), shows good scar.
 15" now 20" D.Fir 65.4 ft. (Rec. 73.3 ft. slope dist-77.6 ft.)

Set Brass cap at cor. mkd: County Surveyors Office
 T31S R1W CC $\frac{S}{S \ 2} \frac{36}{S \ 1}$
 T32S
 1968

Bearing trees OK and tagged.
Record dist. from Angle Point 195.4 ft. I find dist. to be 187.0 ft.