

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 639100

PRIMARY CORNER DESCRIPTION A P on S. bdy S. 36 (W. of ¼ cor.)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Rufus S. Moore, Deputy Surveyor, under Contract #475, dated July 3, 1883 - (DCSO records Vol. 18 Page(s) 7581 & Pg. 7483)

-----  
Set a basalt stone 18x10x6 ins., 12" in the ground for ¼ sec. cor. marked ¼ on N. face, from which  
A Fir 8" dia., bears N.11°E., 12 lks. dist. mkd. ¼ S BT.  
A Fir 12" dia., bears S.32°E., 22 lks. dist. mkd. ¼ S BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7520-21)

-----  
The old ¼ sec. cor. which is a basalt stone firmly set, 6x10x6 ins. above ground, marked ¼ on N. face, from which  
A Fir 12" dia., bears S.32°E., 22 lks. dist. mkd. ¼ S BT.  
(Old BT)

The bearing tree NE. of cor. is dead.  
I now change this cor. to Angle Point; obliterate the marks on the stone and bearing tree and re-mark the tree A P and the stone A P on N. face, from which  
A Fir 16" dia., bears N.71°E., 55 lks. dist. mkd. A P BT.  
(New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - July/Aug. 1968 - C.S. File 54/71-29

-----  
Found - No trace of stone at corner.  
Orig. 12" D.Fir, now dead, S.25°E., 13.0 ft. (Rec. S.32°E., 14.5 ft.) scribe visible "AP BT"  
Orig. 16" now 16" D.Fir N.71°E., 36.3 ft.

Set Brass cap at cor. mkd: County Surveyors Office  
T31S Doug. Co.  
T32S R1W A P  
1968 Jack. Co.

New BT - 38" D.Fir S.49°E., 22.0 ft. mkd. A.P. CS BT.  
Cor. lies 61.4 ft. W. of ¼ cor. Sec. 36, T31-1