

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7553-4)

-----  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  $\frac{S\ 24}{S\ 25}$   
1923

from which

- A fir, 30" dia., bears S.15°W., 15 lks., mkd: 1/4 S25 BT.
- A fir, 22" dia., bears N.17°W., 13 lks., mkd: 1/4 S24 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Sept. 1968 - C.S. File 54/71-66

-----  
Found - No trace of Brass Cap, bladed out in old skid road. 30" D.Fir, now stump, S.15°W., 9.9 ft., shows good scar.

22" D.Fir, now stump, N.17°W., 8.6 ft., opened for scribe.

Set - Brass Cap at Cor. Mkd: County Surveyors T31S R1W  
Office 1968 1/4  $\frac{S\ 24}{S\ 25}$

New BTs- 10" D.Fir S.88°W., 36.3 ft. mkd: 1/4 S25 CS BT.  
9" D.Fir N.24°E., 42.3 ft. mkd: 1/4 S24 CS BT.