

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7556)

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 13}{S\ 24}$
1923

from which

- A fir, 26" dia., bears S.18°E., 28 lks., mkd: 1/4 S24 BT.
- A fir, 16" dia., bears N.52°W., 22 lks., mkd: 1/4 S13 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Oct. 1968 - C.S. File 54/71-81

Found - GLO Brass Cap at 1/4 corner, properly marked in 1922. 26", now 30" D.Fir, S.18°E., 18.5 ft., shows good scar.

16" D.Fir, now stump, N.52°W., 14.5 ft., scribe visible on log by stump, "BT" on stump.

New BT - 15" R.Fir N.21°W., 32.3 ft. scribed 1/4 S13 CS BT.