

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 700109

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 31 only, T31-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7505)

Set an Iron post 3 ft. long, 1" dia., 28" in the ground for 1/4 sec. cor. of sec. 31 only, with brass cap mkd. 1/4 S31

1923

from which

A Fir 16" dia., bears N.4°E., 100 lks. dist. mkd. 1/4 S31 BT

A Fir 18" dia., bears S.56°E., 54 lks. dist. mkd. 1/4 S31 BT

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-65

Found - GLO brass cap at cor., properly mkd. in 1923.
18" now 20" Fir, S.56°E., 35.6 ft., shows good scar.
No trace of NE. BT.

New BT - 8" D.Fir N.26°E., 40.8 ft. scribed "1/4 S31 CS BT".