

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7493-94)

Set a basalt stone 12x10x6 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
 A Fir 30" dia., bears N.37°E., 49 lks. dist. mkd. ¼ S31 BT
 A Fir 30" dia., bears S.55°W., 33 lks. dist. mkd. ¼ S36 BT

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7505)

The ¼ sec. cor. established for secs. 31 and 36, which is a basalt stone, firmly set, 4x10x6 ins. above ground, mkd. ¼ on W. face, from which
 A Fir 30" dia., bears N.37°E., 49 lks. dist. mkd. ¼ S31 BT. (Old BT)
 A Fir 30" dia., bears S.55°W., 33 lks. dist. mkd. ¼ S36 BT. (Old BT)

I now change this cor. to refer to sec. 36 only, and obliterate the marks on the bearing tree referring to S.31. Re-mark the stone ¼ S36 on W. face, from which
 A Fir 10" dia., bears N.87°W., 36 lks. dist. mkd. ¼ S36 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 1968 - C.S. File 54/71

Found - Stone at ¼ corner, faint "¼".
 Orig. 30" now 36" D.Fir, S.55°W., 21.8 ft., shows good scar.
 10" now 13" W.Fir, N.87°W., 23.8 ft., shows good scar.

Set Brass cap at cor. mkd:

	County Surveyors Office
R	T 31 S R
1	S 36 1
W	¼ E
	1968

All BTs. OK and tagged.