

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only (East)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7494)

-----  
Set a basalt stone 14x12x10 ins. 10" in the ground for cor. of secs. 25 and 36, mkd. with 5 notches on N. and 1 notch on S. edges, from which  
A Fir 30" dia., bears S.25°W., 21 lks. dist. mkd. T31S R1W S36 BT.  
A Fir 24" dia., bears N.24°W., 37 lks. dist. mkd. T31S R1W S25 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7506)

-----  
The cor. of secs. 25 and 36 only, which is a basalt stone firmly set, 4x12x10 ins. above ground, marked with 5 notches on N., and 1 notch on S. edge; from which  
A Fir 30" dia., bears S.25°W., 21 lks. dist. mkd. T31S R1W S36 BT. (Old BT)  
A Fir 24" dia., bears N.24°W., 37 lks. dist. mkd. T31S R1W S25 BT. (Old BT)  
Re-mark the stone S36 on SW.; and S25 on NW. faces.

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-58

-----  
Found - Stone at corner, no marks visible.  
30" D.Fir now snag, S.25°W., 13.9 ft. shows good scar.  
24" now 27" R.Fir N.24°W., 24.4 ft., scribe visible "R" and other marks.  
Set Brass cap at cor. mkd: County Surveyors Office  
R T 30 S R  
1 S 25 S30 1  
W S 36 E  
1968  
New BTs- 14" Hemlock S.84°W., 18.5 ft. mkd. T31S R1W S36 CS BT.  
14" D.Fir S.47°E., 24.5 ft. mkd. T31S R1E S30 CS BT