

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 700209

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 30 only, T31-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7507)

Set an Iron post 3 ft. long, 1" dia., 28" in the ground for 1/4 sec. cor. of sec. 30 only, with brass cap mkd: 1/4 S30

1923

from which

A Fir 16" dia., bears S.56°E., 141 lks. dist. mkd. 1/4 S30 BT.

A Fir 34" dia., bears N.14°E., 45 lks. dist. mkd. 1/4 S30 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Oct. 1968 - C.S. File 54/71-55

Found - GLO brass cap properly mkd. in 1923.
16" D.Fir now dead, S.56°E., 26.4 ft. (Rec. 93.1 ft.), shows good scar.
34" now 32" D.Fir N.32°E., 29.7 ft. (Rec. N.14°E.) shows good scar.

New BT - 30" D.Fir S.8 1/2°E., 36.7 ft. scribed 1/4 S30 CS BT.
Trees face toward corner. After search, I did not find any other trees to go with record bearings and distances.