

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 18 Page(s) 7495)

Set a basalt stone 12x8x8 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which

A Fir 40" dia., bears S.55°E., 27 lks. dist. mkd. ¼ S30 BT.

A Fir 40" dia., bears S.75°W., 15 lks. dist. mkd. ¼ S25 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7507)

The ¼ sec. cor. established for secs. 25 & 30, which is a basalt stone, firmly set, 4x8x8 ins. above ground, mkd. ¼ on W. face, from which

A Fir 40" dia., bears S.55°E., 27 lks. dist. mkd. ¼ S30 BT. (Old BT)

A Fir 40" dia., bears S.75°W., 15 lks. dist. mkd. ¼ S25 BT. (Old BT)

I now change this cor. to refer to sec. 25 only, and obliterate the marks on the bearing tree referring to sec. 30. Re-mark the stone ¼ S25 on W. face, from which

A Fir 18" dia., bears N.59°W., 37 lks. dist. mkd. ¼ S25 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-49

Found - No trace of corner stone.

40" D.Fir now stump, S.75°W., 9.9 ft., scribe visible.

18" now 20" D.Fir, N.59°W., 24.4 ft., shows good scar.

Set Brass cap at cor. mkd:

County Surveyors Office
R T 31 S R
1 ¼ S 25 1
W 1968 E

New BT - 30" D.Fir S.20°W., 17.4 ft. scribed ¼ S25 CS BT.