

TOWNSHIP 31 RANGE 01 POINT IDENTIFIER # 700249

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30, T31-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 18 Page(s) 7508)

Set an Iron post 3 ft. long, 2" dia., 28" in the ground for cor. of secs. 19 & 30 only, with brass cap marked:

T31S	T31S
R1W	<u>S 19</u>
S25	S 30
	R1E
	1923

from which

A Hemlock 24" dia., bears N.35°E., 41 lks. dist. mkd. T31S R1E S19 BT.

A Yew 12" dia., bears S.58°E., 20 lks. dist. mkd. T31S R1E S30 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Sept. 1968 - C.S. File 54/71-50

Found - GLO brass cap, properly mkd. in 1923.
12" Yew now 12", S.58°E., 13.2 ft. scribe visible
24" now 27" Hemlock, N.35°E., 27.1 ft., shows good scar.

New BT - 9" Yew, N.44°W., 28.0 ft. scribed T31S R1W S25 CS BT.